



Pitch: 3.81mm(0.150inch)




### SPECIFICATIONS

			CUL	VDE
負載電壓	Rated Voltage	Bemessungsspannung	AC 300V	AC 300V
負載電流	Rated Current	Bemessungsstrom	12A	10A
塑膠本體	Housing Material	Isolierstofftyp	Polyamide66(UL94V-0)	
焊針	Solder Pin	Lötstift	□0.8mm, Brass, Tin plated	
操作溫度	Operating Temperature	Umgebungstemperatur	-40°C to + 105°C	
PC板孔徑	PCB Hole Diameter	Lochdurchmesser	φ1.3mm	
UL File No.	E167040			

### TABLE

Item No.	A(mm)	A(inch)
ME040-38102	8.2	0.324
ME040-38103	12.0	0.474
ME040-38104	15.8	0.624
ME040-38105	19.7	0.774
ME040-38106	23.5	0.924
ME040-38107	27.3	1.074
ME040-38108	31.1	1.224
ME040-38109	34.9	1.374
ME040-38110	38.7	1.524
ME040-38111	42.5	1.674
ME040-38112	46.3	1.824
ME040-38113	50.1	1.974
ME040-38114	53.9	2.124
ME040-38115	57.8	2.274
ME040-38116	61.6	2.424
ME040-38117	65.4	2.574
ME040-38118	69.2	2.724
ME040-38119	73.0	2.874
ME040-38120	76.8	3.024
ME040-38121	80.6	3.174
ME040-38122	84.4	3.324
ME040-38123	88.2	3.474
ME040-38124	92.0	3.624



### PCB Layout

