

Data sheet

261-337

4-CONDUCTOR TERMINAL BLOCK LATERAL MARKING SIDE-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE



Technical data

Package size 200 4*50 pieces.

Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	14 AWG
Number of strands	2
Voltage UL	300/600 V
Voltage CSA	300/600 V
Current UL	15/5 A
Current CSA	20/5 A
Pollution degree	3
Weight	3.83 g
Color	green-yellow
Wiring type	Side-entry
No. of connection Points	4
No. of potentials	1
Height	18 mm
Height	0.709 in
Width	10 mm
Width	0.394 in
Depth	28 mm
Depth	1.103 in
Strip length from	8 mm
Strip length to	9 mm

Data sheet

261-337

**4-CONDUCTOR TERMINAL BLOCK LATERAL MARKING
SIDE-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**

Strip length

0.33 in

Data sheet

261-337

4-CONDUCTOR TERMINAL BLOCK LATERAL MARKING SIDE-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

Approval	Voltage	Current	Approval number	Notes
BV	500	24	07436/C0	
CCA	500	26	DK96-00357	
CSA	300/600	20/5	18677-45	
CSM	500	26	017956	
DEMKO	500	24	120039/02	
Dep.MaE	300	27	CS4590N	
DNV	500	26	E6998	
GL	500	24	17295-00HH	
KEMA	500		92.6446.02	
KR	500	24	HMB05880-EL002	
LR	500	26	91/20242(E3)	
PRS	500	26	TE/1219/880590/98	
RMR	500	26	99.00007.250	
RosTesT	500	26	B09523	
SEMKO	500		9408057	
UL	300/600	15/5	E45172	
VDE	500		208ÜG,Bl.1	

Data sheet

261-337

4-CONDUCTOR TERMINAL BLOCK LATERAL MARKING SIDE-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

Accessories

Item number

ALUMINIUM CARRIER RAIL 1000 MM / 3' 3 IN LONG	210-154
COMB TYPE JUMPER BAR INSULATED	261-402
END PLATE WITH FIXING FLANGE	261-361
END STOP FOR WSB QUICK MARKERS	209-122
Individual wire jumpers	individual jumper
MODULAR TEST PLUG ADAPTER MODULAR	249-139
MOUNTING CARRIER CAN BE USED AS END PLATE	209-137
MOUNTING FOOT WITH SCREW FOR TERMINAL BLOCKS WITH ALIGNABLE FIXINGS	209-123
Open individual wire jumpers ends	individual jumper open end
OPERATING STICKER FOR SIDE-ENTRY PCB TERMINAL BLOCKS	210-188/001-000
OPERATING TOOL TO CONNECT JUMPERS	209-132
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620
TEST ADAPTER-MODULE WITH FIXING FLANGES	261-405
TEST PLUG 2 MM / 0.079 IN WIDE	210-136
TEST PLUG 2.3 MM / 0.091 IN WIDE	210-137